

VOICE-DATA TELEPHONIC INTERFACE CONTROL SYSTEMBackground and Summary of the Invention

5 This is a continuation-in-part of application
Serial No. 481,403 filed February 20, 1990 and entitled
"Voice-Data Telephonic Control System" which was a
continuation-in-part of application Serial No. 312,792
10 filed February 21, 1989 and entitled "Voice-Data
Telephonic Control System" which was a continuation-in-
part of application Serial No. 194,258 filed May 16,
1988 and entitled "Telephonic-Interface Statistical
Analysis System", issued July 4, 1989 as U.S. Patent No.
15 4,845,739, which was a continuation-in-part of applica-
tion Serial No. 018,244 filed February 24, 1987 and
entitled "Statistical Analysis System For Use With
Public Communication Facility", issued December 20, 1988
as U.S. Patent No. 4,792,968, which was a continuation-
in-part of application Serial No. 753,299 filed July 10,
20 1985 and entitled "Statistical Analysis System For Use
With Public Communication Facility", now abandoned.

As the use of computer techniques has steadily
grown, related telephonic communication techniques also
have expanded. In that regard, telephone systems have
25 been developed for effectively transmitting digital data
in forms commonly utilized by computer apparatus. At a

09881391-051301

JMS91

more personal level, the traditional push buttons of telephone instruments have been utilized to provide digital signals at a remote location for both data and control functions. Consequently, various operations have been performed.

In the typical operation of a telephone instrument as a digital input device, voice messages prompt callers to provide data and control signals by actuating the alphanumeric buttons of a conventional telephone. Detailed forms of such systems have been proposed in association with computers to provide various services, and one such system is disclosed in United States Patent No. 4,792,968 issued December 20, 1988, to Ronald A. Katz from an application Serial No. 07/018,244 filed February 24, 1987.

Although traditional systems for interfacing an individual person at a telephone terminal with a computer or data processor have been effective, such systems have been somewhat limited in application. In general, the present invention is based on recognizing the need in such systems to accommodate voice signals as to provide recorded audio data, as for subsequent use. Accordingly, the system of the present invention accommodates a caller to identify digital control signals, digital data signals and audio signals, all in an organized format as to accomplish a record for subsequent processing or use.

To consider a specific example, systems have been proposed in the past for interfacing individual telephone terminals with computers, as for sales applications. Individual callers might dial to accomplish a computer interface, then provide ordering data by actuating the telephone terminal buttons to specify goods or services. One such system is disclosed in a

09881393-061301

co-pending related patent application entitled "Telephone Interface Statistical Analysis System", filed May 16, 1988, and bearing a Serial No. 07/194,258 (now U. S. Patent No. 4,845,739) and a related prior application, now U.S. Patent No. 4,792,968. In the use of such systems, the need is recognized for improved capability regarding audio data.

In general, the present invention comprises a telephone computer interface system accommodating digital and vocal telephonic communication, the system being expanded to accommodate and flag audio data distinct from digital data. In using the disclosed system, either outbound or inbound calling operations attain an interface with a central data processing system. Depending on the course of communication during the interface, various states are implemented for the central system to receive and identify: digital control signals, digital data signals and audio or voice signals. Somewhat conventional operation may involve automated vocal communications to cue the caller and keypad digital communications from the caller. Generally, data received from the caller is set in memory for subsequent use or processing. The data may be addressed as to cue a remote terminal or to isolate a set or subset. Callers may be qualified by automatic number identification (ANI) signals checked against an assigned consumable key number. Thus, the system accommodates flexible control and data accumulation (including cued audio) to accommodate any of various specific interface applications or formats.

Brief Description of the Drawings

In the drawings, which constitute a part of this specification, an exemplary embodiment exhibiting

10981793.051301
FOET90" E6ET8860

various objectives and features hereof is set forth.
Specifically:

FIGURE 1 is a block diagram of a system
constructed in accordance with the present invention;

5 FIGURE 2 is a block and schematic diagram of a
component in the system of FIGURE 1; and

FIGURE 3 is a flow diagram illustrating the
operating process of the structure represented in FIGURE
2.

10

Description of the Illustrative Embodiment

As required, a detailed illustrative embodi-
ment of the present invention is disclosed herein.
However, physical communication systems, data formats
15 and operating structures in accordance with the present
invention may be embodied in a wide variety of forms,
some of which may be quite different from those of the
disclosed embodiment. Consequently, the specific
structural and functional details disclosed herein are
20 merely representative; yet in that regard, they are
deemed to afford the best embodiment for purposes of
disclosure and to provide a basis for the claims herein
which define the scope of the present invention.

Referring initially to FIGURE 1, a series of
25 remote terminals T1-Tn (telephone instruments) are
represented (left). The terminals T1-Tn may be similar
and accordingly only the terminal T1 is shown in any
detail. The indicated terminals T1-Tn represent the
multitude of telephone terminals existing in association
30 with a communication facility CO which may comprise a
comprehensive public telephone network.

The communication facility CO, accommodating
the individual terminals T1-Tn, is coupled to a central
processing station CS generally indicated by a dashed-
35 line block. Within the station CS as illustrated,

09881393-061301

processors are provided to interface the terminals T1-Tn so as to accomplish a desired operating format, and accordingly accumulate data relating to individual callers.

5 Calls to and from the terminals T1-Tn are individually processed in accordance with a specific format to accomplish a data cell or packet. For example, the objective of a call may be to order an item of merchandise to implement a mail-order operation. 10 Similarly, a service may be specified and ordered. Accordingly, the interface accomplishes data as a cell for processing the order. In other exemplary formats, the system may function for public polls, lotteries, auctions, promotions and games.

15 At any instant of time, the collective interface involving the communication system CO and the processing station CS may involve several thousand calls. Accordingly, the station CS may take the form of a sizeable computer or mainframe capable of simul- 20 taneously controlling smaller units or directly operating to process many calls involving individual interfaces. Although numerous possible configurations are available, for purposes of explanation, the central station CS of the disclosed embodiment includes a 25 control unit functioning with a plurality of audio response units and associated individual processors and attended terminals.

Essentially, the system of the present invention accumulates data from the remote terminals T1- 30 Tn in cells, which data may include audio data and digital data (numerical) flagged or otherwise distinguished for subsequent expedient processing. Accordingly, the system enables a person at a terminal (T1-Tn) to provide data in both audio and digital forms. 35 For audio transmissions, the person utilizes the

09881393-061301

telephone handpiece (microphone) while for digital communications, the person utilizes the telephone push buttons (keypad).

Considering the exemplary telephone terminal T1 of FIGURE 1 in greater detail, a handpiece 10 (microphone and earphone) is shown along with a panel 12 provided with a rectangular array of individual push buttons 14 in a conventional configuration. Of course, the handpiece 10 accommodates analog signals while the panel 12 is a digital apparatus. As disclosed in detail below, a person is informed or cued through the handpiece 10 (earphone) to provide data in accordance with a specific format. In accordance herewith, the person may provide signals utilizing either the buttons 14 or the handpiece 10 (microphone).

In conventional telephone structures, alphabetic and numeric designations are provided on the buttons 14. For example, several of the buttons 14 carry three letters along with a decimal digit. Specifically, the button designated with the numeral "2" also carries the letters "A", "B" and "C". Thus, the buttons 14 encompass: the numerals "0-9", the symbols "*" and "#" and the alphabet except for the letters "Q" and "Z".

At this stage, some specific aspects of the communication interface are noteworthy. Essentially, by telephonic dialing, the communication facility CO is coupled selectively to certain of the terminals T1-Tn through audio response units AR1-ARn. For example, as a result of dialing a specific telephone number at one of the remote terminal units T1-Tn, the communication facility CO couples the actuated terminal through one line of several sets of lines LS1-LSn to one of the audio response units AR1-ARn. Note that automatic call distributors may be utilized as well known in the art.

From the audio response units AR1-ARn, incoming lines 20 are received through a coupler 22 for communication with individual interface format processors IP1-IPn. Note that the interface processors IP1-IPn are illustrated as separate and distinct units; however, as mentioned above, it is to be recognized that various structural processing combinations may be used, based on time sharing, parallel processing, compiler techniques, bus technologies and other well known computer techniques to accomplish the objective processing as explained in detail below. In some instances, certain of the structure and functions of the processors IP1-IPn can be variously incorporated in the units AR1-ARn. Of course, specific arrangements and configurations will likely be implemented based on available hardware and software development.

The coupler 22 is also connected to a master control and memory unit 24 which is associatively coupled to a look-up table 25, a consumable key limit unit 27, a subset counter 29 and through a crossbar 26 to each of the processors IP1-IPn. Note that both the function and structure of crossbars for selectively interconnecting multiple parallel structures are well known in the computer arts. For a detailed description of crossbars, see the book, "High-Performance Computer Architecture" by Harold S. Stone, published by Addison-Wesley Publishing Company, 1987.

The coupler 22 essentially functions as a switch as well known in the prior art to establish line couplings from one line of an audio response unit (AR1-ARn) to one of the interface processors IP1-IPn. The operation of the coupler 22 is implemented in association with the control unit 24 which may be programmed to execute control and memory functions as detailed below. Again, the division of functions between the unit 24,

09881393-061301

the units AR1-ARn and the processors IP1-IPn may vary considerably depending on available structures and techniques. The disclosed system is merely exemplary in that regard.

5 Generally, in a sales format, the interface processors IP1-IPn receive basic record data from the unit 24 and order data from the terminals T1-Tn. In a multiple format configuration, program data may be stored in the processors IP1-IPn or supplied from the
10 unit 24. In any event, in accordance with a program or format, a packet of data is collected in a processor IP1-IPn during an interface. After being organized in a cell and flagged, the data packet is returned from an interface processor IP1-IPn to the unit 24 for subsequent use or processing. For outbound operation, the
15 unit 24 functions as an automatic dialer to attain desired connections through the units AR1-ARn in accordance with stored telephone numbers.

 Again, considering a sales format, typically
20 individual data cells or packets of data are organized and returned to the unit 24 for processing which ultimately involves performing a service or instructions for shipping merchandise and billing. In some formats, during the course of interfaces with certain callers,
25 the need may arise for person-to-person oral communication. In accordance herewith, to accommodate that need, the interface processors IP1-IPn may be individually associated through a coupler 30 with an attended terminal AT1-ATn. For processing operations as mentioned above, the terminals AT1-ATn may be connected
30 through a coupling unit 31 to an off-line processor 33, also connected to the control and memory unit 24.

 Recapitulating to some extent, the general
35 operation of the system of FIGURE 1 involves the development and maintenance of individual data packets

00001393-061301

or cells drawn from the unit 24 to the individual processors IP1-IPn during interface communications with individual remote terminals T1-Tn. In the exemplary format as treated below, each data cell manifests a merchandise order identifying specific goods, a specific customer, a shipping destination and other related data. In accordance herewith, data in individual cells may include flagged audio data. In any event, the operation of the system involves the organized accumulation of mail-order data (some of which may be audio) in the unit 24 addressable for subsequent use by the processor 33, as to implement billing and delivery of services or merchandise.

As explained in detail below, the data cells (manifesting individual orders) are developed in the individual processors IP1-IPn. Structural details of an exemplary processor are shown in FIGURE 2 and will now be considered. A cell register 34 (FIGURE 2, center) is divided into fields to illustrate an exemplary data format. Specifically, the cell register 34 defines several separate fields for data components manifesting an exemplary order. Record data for some of the fields may reside in the master control and memory unit 24 (FIGURE 1) before the occurrence of any telephone interface. However, other fields are loaded or modified during the period of the interface with a caller at one of the remote terminals T1-Tn providing elements of the data.

Generally, variously accumulated record data is initially loaded into the cell register 34 from the control and memory unit 24 (FIGURE 1) through a bus 36 (FIGURE 2, right center) that is connected through the crossbar 26 (FIGURE 1) to the unit 24. The same bus 36 accommodates movement of a completed or modified data cell to memory (in the unit 24).

00001303-061301

As suggested above, some fields in the cell register 34, as those pertaining to a specific merchandise order, are always loaded by data resulting from the interface and received through a two-way line 38 (FIGURE 2, upper left). That is, a caller is steered through the interface interval, being prompted or cued to provide responses selectively in the form of:

(1) digital control signals, (2) digital data signals or (3) audio signals. Also, in certain applications digital ANI telephone signals may be received through the line 38 indicating the telephone dialing number of the caller. Specifically, ANI (automatic number identification) signals may be provided from the communication facility CO (FIGURE 1) automatically indicating the telephone number for the calling terminal T1-Tn. The ANI signals may be treated either as control or data signals on being received through an audio response unit (AR1-ARn, FIGURE 1), the coupler 22 and the line 38 (FIGURE 2).

Generally, control signals in the line 38 are utilized for the controlled registration of digital data signals and audio signals as appropriate to each specific interface. Of course, the data and audio signals also are received through the line 38.

For convenience of illustration and explanation, the line 38, connected to the coupler 22 (FIGURE 1) is shown to include two separate communication paths, specifically an outgoing path 40 (FIGURE 2) and an incoming path 42. Of course in practice, the two paths would comprise a common two-way or bidirectional line. For outbound calls, the master control and memory unit 24 (FIGURE 1) supplies dialing signals through the coupler 22 and a unit (AR1-ARn) to the facility CO. As indicated above, an automatic dialer structure is incorporated as well known in the art. On completion of

09881393-061301

a connection to a terminal T1-Tn, the unit 24 actuates a processor IP1-IPn through the crossbar 26. Thus, an addressed data packet is used to advise, inform or cue a person at a connected remote terminal (T1-Tn). In some cases, for example inbound calls, an audio response unit AR1-ARn may perform some preliminary operations, after which calls are referred to a processor IP1-IPn through the coupler. Usually, coupling a remote terminal T1-Tn to a processor IP1-IPn initiates an interface format.

During an interface operation, as with the processor IP1 for example, the connection through the coupler 22 and the audio response unit AR1-ARn remains active. For example, the outgoing communication path 40 (FIGURE 2) is provided with voice signals from a voice generator 44 that is in turn controlled by a processor controller 46. Generally, the controller 46 may possess some substantial computing capability along with storage. Accordingly, it responds to an operating program as disclosed in detail below to accomplish an interface format.

The outgoing communication path 40 of the line 38 also is connected to one of the attended terminals AT1-ATn. The signal route in FIGURE 2 is to the path 40 either from a line 48 or the voice generator 44. With respect to the incoming path 42, signals are provided through a multiplexer 52 to provide various lines L0, L1, L2 or L3 exclusively active. The line L3 or line 50 is coupled to an attended terminal AT1-ATn (FIGURE 1). As indicated above and explained in detail below, under various circumstances, signals from persons at terminals are variously transferred, including transfer to an attended terminal (AT1-ATn, FIGURE 1). Thus, the status of an interface may vary, one status or state designating an interconnection of one of the remote terminals

09681393-061301

T1-Tn with an attended terminal, that is, one of the terminals AT1-ATn.

The status of an interface with a caller is indicated by a status register 56 (FIGURE 2, upper right) which is controlled by the process controller 46 and in turn controls the multiplexer 52. The status register 56 basically comprises a two-bit counter capable of indicating four states to control the lines L0-L3 from the multiplexer 52, as indicated below.

10

		<u>Active</u>
<u>State</u>	<u>Operation</u>	<u>Multiplexer Line</u>
"0"	Cue data signals (digital)	L0
"1"	Cue control signals (digital)	L1
"2"	Cue audio signals	L2
"3"	Actuate live interface	L3

15

The states "0", "1" and "2" indicate operations to prompt persons to provide signals digitally. Alternatively, any of the states may be used merely to inform a person where no response is to be received. As indicated above, in the state "3", the caller speaks directly with an operator to provide information in an audio form. The other states accommodate computer interface signals. Implementing the different states, the multiplexer 52 (controlled by the status register 56) selectively activates one of the four lines L0, L1, L2 or L3 to receive a specific class of signals from the path 42.

25

Generally, the control signals received in the line L1 are applied to actuate the controller 46. The data or information signals received in the lines L0 and L2 are provided to the cell register 34 through a gating network 62 (lower left). Several connections are

30

09881393-061301

involved. The line L3 is coupled to an attended terminal (AT1-ATn, FIGURE 1) through a line 50.

The line L0 (digital data) is connected to the controller 46 and to a movable contact 64 of the gating network 62. The line L1 is connected only to the controller 46. The line L2 (audio) is connected through an audio processor 60 to the controller 46 and to the movable contact 64.

The gating network 62 is illustrated in an electromechanical form for ease of explanation with the movable contact 64 displaceable to engage each of the stationary contacts C1-C11 in sequence. However, in an actual embodiment, a well known analogous solid-state configuration would be employed.

In accordance with the symbolic representation of the gating network 62, the movable contact 64 is driven by a gate control 66 to sequentially encounter stationary contacts C1-C11 which are coupled to fields of the register 34. A mechanical drive connection is indicated by a dashed line 67, the gate control 66 being actuated by the process controller 46 as described in detail below. Somewhat more specifically, the operations directed by the controller 46 are illustrated in FIGURE 3 and will now be considered in detail.

The flow diagram of FIGURE 3 implements an exemplary mail-order format for a sales organization with existing "local" customers of record (identified by telephone number, credit card number, etc.) acceptable for credit transactions. To pursue an example, customers are provided with a "special" catalog from which a single order may be placed for each telephone terminal. Thus, customers are assigned a consumable key of "one" to accordingly limit ordering.

09881393-061301
FOIb790-EGF8860

Calls from customers are coupled through an
 audio response unit, e.g. unit AR1 (FIGURE 1) and the
 coupler 22 to the master control unit 24. In one
 format, the customer is recognized by a telephone number
 manifest by automatic number identification (ANI)
 signals. Customer data is fetched to the consumable key
 limit unit 27 based on the calling telephone number.
 The call is then tested to proceed conditionally on the
 key not being previously used or consumed. The test is
 illustrated by a block 77 (FIGURE 3) and is executed by
 the unit 27 with reference to a field 81 of the data
 packet as shown in the register 34 (FIGURE 2). If there
 has been a previous call, the instant call is terminated
 as indicated. Otherwise, the data cell is fetched from
 the unit 24 to a cell register, e.g. register 34 (FIGURE
 2). The operation is indicated by the block 79 (FIGURE
 3). Thus, calls to a specific format number are limited
 to "one". Of course, consumable keys may be set to
 accomplish any desired limitation with respect to a
 specific format. Format interface operation follows
 approval of a call.

At the beginning of an interface operation,
 the processor involved, e.g. processor IP1 (FIGURE 2) is
 set to state "0" as indicated by the block 80 (FIGURE
 3). That state, also indicated by the status register
 56 (FIGURE 2) controls the processor 46 so that a caller
 is cued for digital data signals to be formed by use of
 the buttons 14 at the caller's remote terminal.
 Specifically, the caller might be cued: "Please
 indicate your first item by keying in the three-digit
 catalog number." The audio is reproduced at the
 terminal.

As will be described in detail below, identi-
 fication for an item is stored in a field 82 (FIGURE 2)
 of the cell register 34. Similarly, color, size and

09881393-061301

code data for selected items are cued and stored in a field 84. Of course, other items may be ordered with the consequence that they are recorded in further of the fields 82 and 84 of the cell register 34. The operation also is represented by the block 86 in FIGURE 3 and might be cued: "Please indicate your next item or push button '3' to indicate you are finished."

At the conclusion of the item ordering, the system sets state "1" (cue control) in the status register 56 (FIGURE 2) as indicated by block 88 (FIGURE 3). Note that the state "1" also may be attained by a period of silence from the caller. In any event, the subsequent operation involves a junction, as indicated by the block 90, a determination to be made by whether or not the caller is a customer of record, e.g. "local account?" As an example, the caller might be cued: "If you have a local account, please push button '1'; if not, please push button '2'." The resulting digital control signals set the course for subsequent operations as implemented by the controller 46. Of course, the indication may be confirmed or originated from the data packet.

If a caller has a local account, for example, implying that the caller's address is in the data packet, the system status is reset to state "0" (cue data) as indicated by block 92. In that event, the system resumes the accumulation of non-vocal digital data by cueing for the card number as indicated by the block 94. Note that with the indication of a local account, a designating code (customer I.D. number) is set in the field 98 of the cell register. Concurrently, the expiration date for the customer's account or card is stored in the field 150. These operations are indicated by the block 100 (FIGURE 3).

09881303-061301
TDET90-ECET8860

The accommodation of other orders involving audio communication will now be considered.

Generally, audio operations involve either the introduction of a person-to-person interface, as for example for a new customer, or audio signal interface, as for example to record a new address for an existing customer. During any format operation, these operations may be actuated variously in combination with digital data control and recording. Such operations may involve proceeding through a block 118 (FIGURE 3, upper left); however, other possibilities exist. One such possibility occurs when a caller indicates that his record address is not correct. Specifically in that regard, the junction block 106 (FIGURE 3, right center) queries "verify address?" The cue or prompt might take the form: "According to our records, you are Mr. John Henry with a billing and shipping address of 10 Beverly, Los Angeles, California." A "no" response results in another test as indicated by the block 120 questioning whether or not the present situation is merely a case of an altered address. If so, the system proceeds from a "yes" determination of the block 120 to obtain an audio record of the new address. As indicated by the block 122, state "2" is set and the caller is cued to state his new address as indicated by the block 124. The address is processed by the audio processor 60 (FIGURE 2) and stored as audio data as indicated by the block 126 (FIGURE 3). The operation then proceeds on the basis of a complete record as indicated by the block 108. Note that in this instance audio data is registered in the cell 34 (FIGURE 2) specifically in voice fields 126 with the status register 56 (FIGURE 2, upper left) indicating state "2". Consequently, the junction block 110 (FIGURE 3, lower right) indicates the presence of audio data with the result that the cell register 34

FOET30-EGET8860

being transferred to a live operator. Please stay on the line as you may win a valuable prize." Immediately, the unit 24 increments the counter 29. If a specified count is attained, e.g. "1000", the caller is awarded a premium.

In the example, if the caller is the thousandth to be transferred, the unit 24 actuates the unit AR1 to produce an announcement: "You have won a \$100 credit for your next order. Please stand by."

If the caller is not the one-thousandth to be transferred, as the transfer is made, the caller is informed: "Sorry, no winner, but here is our operator." Essentially, transferred calls are a subset of callers, involuntarily transferred calls are a sub-subset and winners are still another subset.

Once an operator contact has been established several possibilities exist. One possibility is that the operator completes the contents of the cell register 34 (FIGURE 2) without audio data. Essentially, an operator, active at one of the attended terminals, e.g. terminal AT1 (FIGURE 1) has direct control of the cell register 34 (through the controller 46, FIGURE 2) along with a data display and may be able to enter digital data manifesting the order. That possibility is indicated by the junction block 130 (FIGURE 2), "digital data complete?"

If the data can be completed without audio record signals, the system operation proceeds to the block 108 (record complete). If the order record is not completed void of audio data, operation proceeds in state "3". Again, under control of a live operator, the system may follow different paths to produce an ultimate determination of whether or not the audio data provides a complete order as indicated by the decision block 134. In that regard, an operator may perfect an order record

09881393-061301

Note that the initial phase of an inbound call may be variously implemented. For example, call signals provided to an audio response unit AR1-ARn may include representations of the caller's number and accordingly access a file on the caller. In accordance with automated number identification equipment designated ANI embodied in the communication facility CO, the caller's number may be provided in a digital form. The master control and memory unit 24 then accesses the caller's cell accordingly to address individual caller data. As described above, the data may be tested before transfer to the cell register 34 with the interface being conditioned on the test. That is, as indicated above, a customer may be limited to a specified number of order calls with regard to a particular catalog or offer. Thus, the interface may involve several tests, one of which is preliminary to setting the addressed customer data in the register 34. An example will illustrate.

An offering may be made to potential customers regarding goods or services in limited amounts. For example, customers might be offered one or two purchases, but no more. Accordingly, the data cells for such customers would be set to allow only one or two purchases as specified. Specifically, for example, the field 81 (key number) for each potential customer key number would be set at "one". Upon the occurrence of a call by a customer, an individual associated data cell would be addressed using the caller's telephone number provided by automatic number identification (ANI) equipment.

From within the master control and memory unit 24, the field 81 (key number) of the cell would be checked by the consumable key limit unit 27. If the consumable key number had been reduced to "zero" or incremented to "one" as programmed to indicate a previous call, the call would be rejected by the active audio response unit

09881393-061301

AR1-ARn. Otherwise, the call would be accepted and the consumable key number would be incremented or decremented by the unit 27.

5 With the acceptance of the call, the data cell would be set in a cell register of a selected interface format processor, e.g. processor IP1, register 34 (FIGURE 2). The direct interface would then proceed.

10 Recognizing the various possibilities, assume that at the outset of the direct interface, the voice generator 44 (FIGURE 2, upper left) is actuated by the process controller 46 to greet the caller. For example, the voice generator 44 might cue the caller as follows:
 15 "Thank you for calling XYZ COMPANY telephone merchandise service. Please push three buttons on your telephone to identify your first item by catalog number."

Signals representative of three decimal digits identifying an item are supplied from the line 42 (FIGURE 2, upper left) to the multiplexer 52. As the status register 56 is in the "0" state, the signals pass
 20 from the multiplexer 52 through the moving contact 64 and the stationary contact C1 to be registered in field 82, "item".

In the illustrative format, the customer next is prompted to digitally enter data indicating choices
 25 of color, size, special code and so on. For receiving such data, the gate control 66 actuates the gating network 62 in synchronism with the cue to the second position so that the item data is provided through the contact C2 to the field 84. Following a similar
 30 pattern, the caller may identify several item designations which are registered in the item fields 82 and 84 of the cell register 34. Note that items are checked in relation to inventory by the controller 46 acting through the unit 24 (FIGURE 1) and the associated
 35 inventory look-up table 25.

the stationary contact C4, and the customer's number is stored in the field 98.

As an alternative to the caller's telephone number for addressing individual data, the customer's number may be utilized. In either event, individual data cells are addressed for record data to load other fields, e.g. fields 150, 152, 154, etc. Generally, if a record for the customer's card is located in the unit 24 (FIGURE 1), the information is returned via the bus 36 (FIGURE 2, right center) and registered in the cell register 34. Alternatively, the data may be confirmed by the caller and entered through the gating network 62.

In the disclosed embodiment, the data includes the expiration date of the card placed in field 150, the customer's telephone number set in field 152 and the customer's name and address set in the field 154. The telephone number may be useful if a live interface is prompted or, as indicated above, it may be used as an address to locate a particular file or data.

Considering the stage-by-stage confirming operation, the location of a customer's record prompts the controller 46 (FIGURE 2) to actuate the gate control 66 setting the movable contact 64 to dwell in sequence at the contacts C5, C6 and C7. With confirmation, the customer's card expiration date, telephone number and address are supplied to the fields 150, 152 and 154. For example, the customer's address is supplied from the controller 46 to the voice generator 44. Consequently, as indicated above, the caller might be prompted as follows: "According to our records, you are Mr. John Henry with a billing and shipping address of 10 Beverly, Los Angeles, California. If our information is correct, please push '1'; if not, please push '2'." This operation is symbolized in FIGURE 3 by the block 106 (right center).

1001393-061301

operations to: place related calls, fill orders and bill charges. Specifically for example, referring to FIGURE 1, the manually attended terminals AT1-ATn may be actuated to control the processor 33 through the coupling unit 31. The processor 33 is operated in cooperation with the unit 24 to process individual orders. Note that the audio data stored in cells is flagged for selection as explained in detail below.

To illustrate an alternate course in the process as generally described above, assume that the customer has a valid credit card record with the XYZ COMPANY; however, the address of record is incorrect. In processing an interface with such a customer, the operation would be as described above except that the junction represented by the block 106 (FIGURE 3, right center) would determine an incorrect address. Consequently, with the system in state "1", a control signal manifesting an incorrect address is supplied through the line L1 to the process controller 46 setting up an alternate operation. Specifically, the next step involves determining whether the verification failure may be corrected by a mere change of address as indicated by the block 120 (FIGURE 3). To implement the operation, the process controller 46 (FIGURE 2) actuates the voice generator 44 to cue the caller for control signals. For example, the cue may be stated: "If it is simply a matter of correcting or changing your address, please push '1'. Otherwise, push '2'."

If the caller actuates the "1" button, a control signal is provided through the multiplexer 52 and the line L1 to the process controller 46 indicating a simple address correction. As a result, the process controller 46 sets the status register 56 to state "2" (see block 122, FIGURE 3). As a consequence, in the system of FIGURE 2, the input path 42 is coupled through

09881393-061301

contemplated to involve human processing to convert spoken words to digital data.

To pursue another possible course of operation, assume that prompting or cueing a customer regarding his altered address does not involve a mere change. That is, assume the decision block 120 (FIGURE 3, central) produced a control signal manifesting "no", i.e. more than a mere change is involved and a live contact interface is desirable. Upon such an occurrence, state "3" is set as indicated by the block 118 (FIGURE 3). As indicated above, several other possibilities may set the operation of state "3": In any event, the status register 56 (FIGURE 2) is set by the controller 46 to manifest state "3". Consequently, the status register 56 controls the multiplexer 52 actuating communication through the line L3 to the lines 48 and 50 coupled to one of the attended terminals AT1-ATn (FIGURE 1).

In the configuration of state "3", the process controller 46 along with the lines 48 and 50 are linked to one of the attended terminals AT1-ATn enabling an operator to speak directly with a caller and concurrently set data into the data cell register 34 through the controller 46. Note that the attended terminals AT1-ATn include a display and, accordingly, the controller 46 cooperatively drives the display with the cell register to indicate the state of the interface and the caller's data. Thus, unconventional orders are processed with the system in state "3" as described above, the process flowing from the block 118 (FIGURE 3, upper left).

Of course, numerous possibilities exist for completing an order with an attended terminal. In that regard, the contents and control of the cell register 34 is by the attended terminal and the problem may simply

098133-0613860

be one of communication in which case the order data may be completed either with or without audio data.

Recapitulating to some extent, a live interface is prompted from several situations. One case involves the caller depressing the "*" button. Also, if the caller does not have credit with the XYZ COMPANY (not a local account) a live interface is prompted. In that regard, an alternative credit card as a bank card may be employed. Accordingly, data is received in either an audio or non-audio form.

Consider a bank credit card order with reference to FIGURE 2 in which the cell register 34 receives alternate information. In this situation, the field 96 may store an indication of an acceptable bank card. Specifically, fields 96, 98 and 150 respectively store a bank card type, the bank card number and the expiration date. It may be further advisable to store the caller's telephone number in field 152. The caller's name and address will be stored; and in that regard, either the field 154 may be utilized by the operator at an attended terminal or an audio record may be keyed for storage in one or more fields 126. If the order is completed by an operator, the system proceeds as explained above with the final steps of indicating an acknowledgement number and designating the class of the order. Thereafter, as in other examples, the contents of the cell register is returned to the master control and memory unit 24 (FIGURE 1) for subsequent processing. Note, class "1" orders also may be stored, as in a processor IP1-IPn until completed (without audio data).

It may be seen that the system accomplishes telephonic interfaces utilizing various operations in accordance with control signals prompted by cues from a voice generator. That is, the system alternately may cue a caller to provide: digital data, control data or

09881393-061301
10E190-EEET8860

